



SAFETY DATA SHEET

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION



PRODUCT NAME: M90-0310 / M90-1010
PRODUCT CLASSIFICATION: Silicone Sealant
DATE: 6/23/2015
GENERAL DESCRIPTION: Silicone elastomer
PHYSICAL FORM: Paste
COLOR: Clear
ODOR: Acetic acid odor
NFPA PROFILE: Health – 1 Flammability – 1 Instability/Reactivity – 0
MANUFACTURER: **COMPONENT HARDWARE GROUP, INC.**
1890 SWARTHMORE AVENUE
LAKEWOOD, NJ 08701
TEL. 800-526-3694, 732-363-4700 / FAX 732-364-8110
IN CAST OF EMERGENCY: **U.S.:** 800-526-3694
EUROPE: 31-76-5968-69

SECTION 2. HAZARDS IDENTIFICATION

PHYSICAL HAZARDS: Not classified
HEALTH HAZARDS: Reproductive toxicity (fertility) Category 2
ENVIRONMENTAL HAZARDS: Not classified
OSHA DEFINED HAZARDS: Not classified

Hazards not stated here are "Not Classified", "Not Applicable" or "Classification Not Possible".

GHS LABEL ELEMENTS

SIGNAL WORD: Warning  

HAZARD STATEMENT: Suspected of damaging fertility.

PRECAUTIONARY STATEMENT: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

PREVENTION: Wear protective gloves/protective clothing/eye protection/face protection. Wash well after handling. Contaminated work clothing should not be allowed out of work place.

RESPONSE: **SKIN:** Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention/advice. Get medical attention/advice if you feel unwell.
EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritant persists get medical attention/advice.
If exposed or concerned: Get medical attention or advice. Take off contaminated clothing and wash it before reuse.

STORAGE: Store locked up.

DISPOSAL: Dispose of contents/container in accordance with local/regional/state/federal and international regulations.

HAZARD(S) NOT OTHERWISE CLASSIFIED (HNOC): None known.

SUPPLEMENTAL INFORMATION: None known.

SUBSTANCE(S) FORMED UNDER THE CONDITIONS OF USE: This product reacts with water, moisture or humid air to evolve following compounds: Acetic acid. The following material is embedded in the product and not available as respirable dusts. When used as intended or as supplied, the product will not pose hazards. Titanium oxide.

HMIS (RATINGS): Health: 1 Flammability: 1 Physical Hazard: 0



MATERIAL SAFETY DATA SHEET

SECTION 3. COMPOSITION / INGREDIENTS

MIXTURES

HAZARDOUS INGREDIENTS:

CHEMICAL NAME	CAS NUMBER	%
Ethyltriacetoxysilane	17689-77-9	1 - 5
Methylacetoxysilane	4253-34-3	1 - 5
Titanium Oxide	13463-67-7	< 1
Distillates (petroleum), hydrotreated middle	64742-46-7	1 - 7
Octamethylcyclotetrasiloxane (impurity)	556-67-2	< 1

SECTION 4. FIRST AID MEASURES

INHALATION:	Move to fresh air. Call a physician if symptoms develop or persist.
SKIN CONTACT:	Wash off with soap and plenty of water. For minor skin contact, avoid spreading material on unaffected skin. If skin irritation or rash occurs: get medical attention/advice. Take off contaminated clothing and wash before use.
EYE CONTACT:	Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation developed or persists.
INGESTION:	Wash out mouth. Get medical attention immediately.
MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:	Direct contact with eyes may cause temporary irritation.
INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:	Treat symptomatically.
GENERAL INFORMATION:	If exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of materials involved and take precautions to protect themselves. Wash contaminated clothing before reuse.

SECTION 5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂)
UNSUITABLE EXTINGUISHING MEDIA:	None known.
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:	By heating and fire, harmful vapors/gases may be formed.
SPECIFIC PROTECTIVE EQUIPMENT / PRECAUTIONS FOR FIREFIGHTERS:	Firefighters must use standard protective equipment including flame retardant coat, helmet, gloves, rubber boots and self-contained breathing apparatus.
FIRE FIGHTING EQUIPMENT / INSTRUCTIONS:	Move containers from fire area if you can do so without risk.
GENERAL FIRE HAZARDS:	No unusual fire or explosion hazards noted.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS / PROTECTIVE EQUIPMENT / EMERGENCY PROCEDURES:	Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch or walk through spilled material. Ensure adequate ventilation. Wear appropriate personal protective equipment.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP:	Eliminate sources of ignition. Large Spills: Dike the spilled material where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for reuse.
ENVIRONMENTAL PRECAUTIONS:	Prevent further leakage or spillage if safe to do so.



MATERIAL SAFETY DATA SHEET

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Provide adequate ventilation. Use care in handling/storage. Obtain special instructions before use. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Pregnant and breastfeeding women must not handle this product. Do not breathe the mist or vapor. Avoid contact with eyes. Avoid contact with skin. Avoid long term exposure.

CONDITIONS FOR SAFE STORAGE INCLUDING ANY INCOMPATIBILITIES: Store locked up. Keep container tightly closed. Keep out of reach of children. Store in a cool dry place out of direct sunlight. Keep in original container.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

U.S. OSHA TABLE Z-1 LIMITS FOR AIR CONTAMINANTS (29 CFR 1910.1000)

COMPONENTS	CAS #	TYPE	VALUE
Titanium Oxide	13463-67-7	PEL	15 mg/m ³
DECOMPOSITION			
Acetic Acid	64-19-7	PEL	25 mg/m ³ 10 ppm

U.S. ACGIH THRESHOLD LIMIT VALUES

COMPONENTS	CAS #	TYPE	VALUE
Titanium Oxide	13463-67-7	TWA	10 mg/m ³
DECOMPOSITION			
Acetic Acid	64-19-7	STEL TWA	15 ppm 10 ppm

U.S. NIOSH: POCKET GUIDE TO CHEMICAL HAZARDS

DECOMPOSITION	CAS #	TYPE	VALUE
Acetic Acid	64-19-7	STEL TWA	37 mg/m ³ 15 ppm 25 mg/m ³ 10 ppm

BIOLOGICAL LIMIT VALUES: No biological exposure limits for the ingredient(s).

APPROPRIATE ENGINEERING CONTROLS: Provide adequate general and local exhaust. Provide eyewash station. Pay attention to ventilation such as local exhaust, mechanical and or / door open for at least 24 hours after applications.

INDIVIDUAL PROTECTION MEASURES SUCH AS PERSONAL PROTECTIVE EQUIPMENT

EYE / FACE PROTECTION: Tightly sealed safety glasses according to EN 166.

SKIN / HAND PROTECTION: Wear protective gloves.

OTHER: Wear suitable protective clothing.

RESPIRATORY PROTECTION: If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

THERMAL HAZARDS: Wear appropriate thermal protective clothing when necessary.

GENERAL HYGIENE CONSIDERATIONS: Avoid contact with eyes. Avoid contact with skin. When using, do not eat, drink or smoke. Keep away from food or drink. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the work place. Handle in accordance with good industrial hygiene and safety practice.



MATERIAL SAFETY DATA SHEET

SECTION 9. PHYSICAL/ CHEMICAL CHARACTERISTICS

MELTING/FREEZING POINT: N/A	BOILING POINT: N/A	FLASH POINT: 141.8°F (>96°C)
RELATIVE DENSITY (25°C): 1.04	VAPOR DENSITY (AIR=1): >1	VAPOR PRESSURE (25°C): Negligible
EVAPORATION RATE (Butyl Acetate=1): <1	SOLUBILITY (WATER): Not soluble	FLAMMABILITY (SOLID, GAS): N/A
FLAMMABILITY LIMIT LOWER (%): N/D	FLAMMABILITY LIMIT UPPER (%): N/D	PARTITION COEFFICIENT: N/A
EXPLOSIVE LIMIT LOWER (%): N/A	EXPLOSIVE LIMIT UPPER (%): N/A	AUTO-IGNITION TEMPERATURE: N/D
DECOMPOSITION TEMPERATURE: N/A	VISCOSITY: N/A	MOLECULAR WEIGHT: N/A
pH: N/A	ODOR THRESHOLD: N/A	
APPEARANCE – FORM / COLOR / ODOR:	Clear colored paste with acetic acid odor.	

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY:	No hazardous reaction known under normal conditions of use, storage and transport.
CHEMICAL STABILITY:	Stable at normal conditions.
POSSIBILITY OF HAZARDOUS REACTIONS:	Hazardous polymerization does not occur.
CONDITIONS TO AVOID:	None known.
INCOMPATIBLE MATERIALS:	Strong oxidizing agents. Water and moisture.
HAZARDOUS DECOMPOSITION PRODUCTS:	This product reacts with water, moisture, or humid air to evolve following compounds. Acetic acid. Thermal breakdown of this product during fire or very high heat condition may evolve the following hazardous decomposition product: Carbon dioxides and traces of incompletely burned carbon compounds. Silicone dioxide. Formaldehyde.

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE

INGESTION:	Expected to be a low ingestion hazard.	SKIN CONTACT:	No adverse effects due to skin contact are expected.
INHALATION:	Prolonged inhalation may be harmful.	EYE CONTACT:	Direct contact with eyes may cause temporary irritation.
SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL, AND TOXICOLOGICAL CHARACTERISTICS:		Direct contact with eyes may cause temporary irritation.	

INFORMATION ON TOXICOLOGICAL EFFECTS – ACUTE TOXICITY, TOXICOLOGICAL DATA:

DECOMPOSITION	CAS #	SPECIES	TEST RESULTS
Acetic Acid	64-19-7		
Acute Dermal LD50		Rabbit	1060 mg/kg
Inhalation LC50		Guinea Pig	5000 ppm, 1 hour
		Mouse	5620 ppm, 1 hour
		Rat	11.4 mg/l, 4 hours
Oral LD50		Mouse	4960 mg/kg
		Rabbit	1200 mg/kg
		Rat	3.31 g/kg

SKIN CORROSION / IRRITATION:	Causes severe skin burns and eye damage. (Acetic Acid) Skin - Rabbit: 500 mg/24hr. MILD (Octamethylcyclotetrasiloxane)
SERIOUS EYE DAMAGE / EYE IRRITATION:	Causes serious eye damage. (Acetic Acid) Eye - Rabbit: MILD (Octamethylcyclotetrasiloxane)
RESPIRATORY SENSITIZATION:	N/A
SKIN SENSITIZATION:	No evidence of sensitization (Octamethylcyclotetrasiloxane)
GERM CELL MUTAGENICITY:	Negative (Bacteria) (Octamethylcyclotetrasiloxane)
CARCINOGENICITY:	Titanium oxide is embedded in the product and not available as respirable dusts. When used as intended or as supplied, the product will not pose hazards.



MATERIAL SAFETY DATA SHEET

IARC MONOGRAPHS, OVERALL EVALUATION OF CARCINOGENICITY:

Titanium Oxide (CAS 13463-67-7)
2B Possibly carcinogenic to humans.

OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910.1..1-1050):

Not listed

REPRODUCTIVE TOXICITY:

Octamethylcyclotetrasiloxane administered to rats by whole body inhalation at concentrations of 500 and 700 ppm for 70 days prior to mating, through mating, gestation and lactation resulted in decreases in live litter size. Additionally, increases in the incidence of deliveries of offspring extending over an unusually long time period (dystocia) were observed at these concentrations. Statistically significant alterations in these parameters were not observed in the lower concentrations evaluated (300 and 70 ppm). In a previous range-finding study, rats exposed to vapor concentrations of 700 ppm had decreases in the number of implantation sites and live litter size. The significance of these findings to humans is not known. (Octamethylcyclotetrasiloxane)

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE:

N/A

SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE:

Repeated inhalation or oral exposure of mice and rats to Octamethylcyclotetrasiloxane produced an increase in liver size. No gross histopathological or significant clinical chemistry effects were observed. An increase in liver metabolizing enzymes, as well as a transient increase in the number of normal cells (hyperplasia) followed by an increase in cell size (hypertrophy) were determined to be the underlying causes of the liver enlargement. The biochemical mechanisms producing these effects are highly sensitive in rodents, while similar mechanisms in humans are insensitive. A two year combined chronic and carcinogenicity assay was conducted on Octamethylcyclotetrasiloxane. Rats were exposed by whole-body vapor inhalation 6hrs/day, 5 days a week for up to 104 weeks to 0, 10, 30, 150, 700 ppm of Octamethylcyclotetrasiloxane. The increase in incidence of (uterine) endometrial cell hyperplasia and uterine adenomas (benign tumors) were observed in female rats at 700 ppm. Since these effects only occurred at 700 ppm, a level that greatly exceeds typical workplace or consumer exposure, it is unlikely that industrial, commercial or consumer uses of products containing Octamethylcyclotetrasiloxane would result in a significant risk to humans. (Octamethylcyclotetrasiloxane)

ASPIRATION HAZARD:

N/A

CHRONIC EFFECTS:

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

FURTHER INFORMATION:

This product reacts with water, moisture or humid air to evolve following compounds: Acetic Acid.

SECTION 12: ECOLOGICAL CONSIDERATIONS

ECOTOXICITY: Octamethylcyclotetrasiloxane: May cause long lasting harmful effects to aquatic life.

COMPONENTS:

Titanium Oxide
(CAS 13463-67-7)

SPECIES

TEST RESULTS

AQUATIC:

Crustacean
Fish

EC50
LC50

Water Flea (Daphnia Magna)
Mummichog (Fundulus Heteroclitus)

>1000 mg/l, 48 hours
>1000 mg/l, 96 hours

DECOMPOSITION:

Acetic Acid
(CAS 64-19-7)

AQUATIC:

Crustacean
Fish

EC50
LC50

Water Flea (Daphnia Magna)
Bluegill (Lepomis Macrochirus)

65 mg/l, 48 hours
75 mg/l, 96 hours

PERSISTENCE AND DEGRADABILITY: N/A

BIOACCUMULATIVE POTENTIAL: Bio Concentration Factor (BCF) / (Flathead Minnow): 12400 Octamethylcyclotetrasiloxane.

MOBILITY IN SOIL: N/A

OTHER ADVERSE EFFECTS: N/A

SECTION 13: DISPOSAL CONSIDERATIONS

Can be land-filled for cured product or burned in a chemical incinerator equipped with an afterburner and scrubber. Do not dispose the emptied container unlawfully. Observe all federal, state and local laws.



MATERIAL SAFETY DATA SHEET

SECTION 14: TRANSPORT INFORMATION

DOT: Not regulated as dangerous good.
IATA: Not regulated as dangerous good.
IMDG: Not regulated as dangerous good.
TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPDL 73/78 AND THE IBC CODE: This product is not intended to be transported in bulk.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910.1001-1050): Not listed.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) SARA 313 (TRI REPORTING)

US STATE REGULATIONS

- MASSACHUSETTS: SUBSTANCE LIST:** Titanium Oxide (CAS 13463-67-7)
- NEW JERSEY WORKER AND COMMUNITY RIGHT TO KNOW ACT:** Titanium Oxide (CAS 13463-67-7)
- PENNSYLVANIA WORKER AND COMMUNITY RIGHT TO KNOW ACT:** Titanium Oxide (CAS 13463-67-7)
- RHODE ISLAND RTK:** Not regulated.
- CALIFORNIA PROPOSITION 65:** The following material is embedded in the product and not available as respirable dusts. When used as intended or as supplied, the product will not pose hazards.

- US CALIFORNIA PROPOSITION 65 - CRT: LISTED DATE / CARCINOGENIC SUBSTANCE

Titanium Oxide (CAS 13463-67-7) Listed: September 2, 2011

INTERNATIONAL INVENTORIES

COUNTRY(S) OR REGION	INVENTORY NAME	ON INVENTORY (YES/NO)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemicals	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
United States	Toxic Substances Control Act (TSCA) Inventory	Yes

* A "YES" indicates that all components of this product comply with the inventory requirements administered by the governing country. A "NO" indicates that one or more components of the product are not listed or exempted from listing on the inventory administered by the governing country.



MATERIAL SAFETY DATA SHEET

SECTION 16: OTHER INFORMATION

PREPARED BY: COMPONENT HARDWARE GROUP, INC.
ISSUE DATE: 6/23/2015
REVISION DATE: —
FOR ASSISTANCE ON THIS PRODUCT IN EUROPE: **CHG EUROPE B.V.**
Hazeldonk 6475
4836 LH Breda
The Netherlands
Tel. 31-76-5968-69, Fax. 31-76-5963-114

This data is offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.